


# Suspended Linear LED Lighting



## Specifications

- 3 length options: 600mm = 18W | 1200mm = 36W | 1500mm = 45W
- Natural White (4000K) or Warm White (3000K) LED colour
- Supplied with 1.5m suspension and surface mount kits
- Finished in White RAL9010 (other options available)
- Optional Integrated Emergency Kit
- Integrated LED Driver

Model Number	Length (mm)	CCT	Wattage	Lumen	Beam Angle	IP Rating	CRI	PF	Voltage
STL137-600-4000	606	4000K	18W	1447lm	110°	IP40	> 80	> 0.95	100-240V
STL137-600-3000	606	3000K	18W	1283lm	110°	IP40	> 80	> 0.95	100-240V
STL137-1200-4000	1206	4000K	36W	2977lm	110°	IP40	> 80	> 0.95	100-240V
STL137-1200-3000	1206	3000K	36W	2516lm	110°	IP40	> 80	> 0.95	100-240V
STL137-1500-4000	1506	4000K	45W	3375lm	110°	IP40	> 80	> 0.95	100-240V
STL137-1500-3000	1506	3000K	45W	2672lm	110°	IP40	> 80	> 0.95	100-240V

Add to model number: D for Traic Dimmable, DALI for DALI Dimmable, EM for Integrated Emergency Pack (not available in 600mm)

