


## Slim Recessed Linear Lighting



### Specifications

- 3 length options: 600mm = 18W | 1200mm = 24W | 1500mm = 36W
- Recessed mounted (supplied with Spring Clips)
- Natural White (4000K) or Warm White (3000K)
- Aluminium profile finished in White (RAL 9010)
- Optional Emergency Kit and Dimmable Drivers
- Integrated LED Driver (the optional dimmable drivers are external)

Model Number	Length (mm)	Cut Out (mm)	CCT	Wattage	Lumen	Beam Angle	IP Rating	CRI	PF	Voltage
STL278-600-4000	616	606 x 37	4000K	18W	1412lm	110°	IP40	> 80	> 0.95	100-240v
STL278-600-3000	616	606 x 37	3000K	18W	1197lm	110°	IP40	> 80	> 0.95	100-240v
STL278-1200-4000	1216	1206 x 37	4000K	24W	1727lm	110°	IP40	> 80	> 0.95	100-240v
STL278-1200-3000	1216	1206 x 37	3000K	24W	1568lm	110°	IP40	> 80	> 0.95	100-240v
STL278-1500-4000	1516	1506 x 37	4000K	36W	2793lm	110°	IP40	> 80	> 0.95	100-240v
STL278-1500-3000	1516	1506 x 37	3000K	36W	2439lm	110°	IP40	> 80	> 0.95	100-240v

Add to model number: D for Traic Dimmable, DALI for DALI Dimmable, EM for Emergency Pack

