

Tubular 60 track light

Product Data





This commercial 13W LED Track Light is available in a wide choice of options. Choose from black or white housing with a further selection of baffle colour in gold, black or white. A Global Trac Pro 3-Circuit adapter is used allowing attachment to Global and compatible track systems e.g. Powergear (this does not apply to the DALI option). A high quality, versatile and flexible LED spotlight with many applications in shops, offices, showrooms, community and domestic premises.

Technical Data

Housing Material - Aluminium Light Source - Integral LED 13W Colour Temperature - 2700K, 3000K, 4000K CRI - 90

Beam Angle - 15°, 24°, 36°, 50°

Light Output - see table below

Input - 200V-240V

Track Adapter - Global 3-Circuit

Colour Finish - Black, White

Baffle Finish - Black, White, Gold

IP Rating - IP20

Dimensions - diameter 63mm x height 170mm

Dimming Options - mains dimming (standard), DALI (optional)

Optional Extra - Honeycomb Diffuser





TUBULAR 60 LUMENSHEET

90CRI 2700K / 350mA / 13W	15°	24°	36°	50°
DELIVERED OUTPUT	1051lm	1303lm	1278lm	1208lm
90CRI 3000K / 350mA / 13W DELIVERED OUTPUT	15°	24°	36°	50°
	1109lm	1360lm	1334lm	1261lm
90CRI 4000K / 350mA / 13W DELIVERED OUTPUT	15°	24°	36°	50°
	1175lm	1429lm	1402lm	1325lm

