

Tubular 60 pendant fixed

Product Data



This commercial 13W LED Pendant Light is available in a wide choice of options. Choose from black or white housing with a further selection of baffle colour in gold, black or white. The light comes with a rose for surface mounting on a ceiling. A high quality, versatile and flexible LED spotlight with many applications in shops, offices, showrooms, community and domestic premises.

Technical Data

Housing Material - Aluminium
Light Source - Integral LED 13W
Colour Temperature - 2700K, 3000K, 4000K
CRI - 90
Beam Angle - 15°, 24°, 36°, 50°
Light Output - see table below
Input - 200V-240V
Ceiling Rose (see below)
Colour Finish - Black, White
Baffle Finish - Black, White, Gold
IP Rating - IP20
Dimensions - diameter 63mm x height 160mm
Dimming Options - mains dimming (standard), DALI (optional)
Optional Extra - Honeycomb Diffuser



TUBULAR 60 LUMENSHEET

90CRI 2700K / 350mA / 13W	15°	24°	36°	50°
DELIVERED OUTPUT	1051lm	1303lm	1278lm	1208lm
90CRI 3000K / 350mA / 13W	15°	24°	36°	50°
DELIVERED OUTPUT	1109lm	1360lm	1334lm	1261lm
90CRI 4000K / 350mA / 13W	15°	24°	36°	50°
DELIVERED OUTPUT	1175lm	1429lm	1402lm	1325lm

