

Mains Dimmable Track Adapter

Product Information



INPUT	220-240VAC			
OUTPUT	CONSTANT CURRENT			
OUTPUT CURRENT	200mA (8W)	250mA (10W)	300mA (12W)	350mA (14W)
	650mA (24W)	700mA (26W)	750mA (28W)	800mA (32W)

DIMMING RANGE 10%-100%

OUTPUT VOLTAGE 27-40V

IP RATING IP20

MAX OUTPUT POWER 32W

FREQUENCY 50/60Hz

START DELAY TIME ≤0.5S (230VAC - FULL LOAD)

INPUT CURRENT ≤0.23A

DIMENSIONS L196 x W31 x H45 & L250 x W31 x H45

TYPE	CONNECTED QUANTITIES OF DIFFERENT CURRENT BREAKER						INPUT VOLTAGE	INRUSH CURRENT	TIME
	CURRENT (A)	10	13	16	20	25			
	WIRE DIAMETER	1.5MM ²	2.5MM ²	2.5MM ²	4.0MM ²	4.0MM ²	230VAC	40	500us
	TYPE B	15	20	24	30	38			
	TYPE C	24	31	38	48	60			
	TYPE D	38	50	61	77	96			

COMPATIBLE WITH:

GLOBAL [®]

EUTRAC

ERCO

A. A. G.
 STUCCHI
 Follow your illumination

unipro [®]