

# STL150

DIRECT SUSPENDED LINEAR



The STL150 is an elegantly designed ceiling-mounted LED luminaire that offers direct light distribution. It features a sturdy anodized aluminium housing available in black or white satin finishes. The UV-stabilized frosted diffuser ensures optimal light transmittance while reducing glare. This fixture comes with a switchable driver integrated into the housing, and you can opt for a DALI driver and/or a 3-hour emergency pack for added functionality. It is available in two colour temperatures—3000K or 4000K—with LED PCB boards boasting a CRI greater than 80, ensuring vibrant and accurate colour rendering.

## Product Information

LENGTH OPTIONS:	POWER:	COLOUR TEMPERATURE:	OUTPUT:	EFFICIENCY:
600mm	14W	3000K	1345lm	96lm/w
600mm	14W	4000K	1402lm	100lm/w
900mm	21W	3000K	2040lm	97lm/w
900mm	21W	4000K	2111lm	100lm/w
1200mm	26W	3000K	2585lm	99lm/w
1200mm	26W	4000K	2648lm	101lm/w
1500mm	32W	3000K	3230lm	100lm/w
1500mm	32W	4000K	3318lm	103lm/w

<b>BODY:</b>	White ● Black	<b>LIFETIME:</b>	60,000hrs
<b>COLOUR TEMPERATURE:</b>	3000K ● 4000K	<b>DIFFUSER:</b>	UV Frosted
<b>DIMMING:</b>	Switched ● DALI	<b>INPUT:</b>	230-240V
<b>CRI:</b>	>80	<b>MATERIAL:</b>	Anodised Aluminium
<b>IP RATING:</b>	IP40		
<b>EMERGENCY:</b>	3hr Kit (Optional)		
<b>BINNING SDCM:</b>	3		
<b>UGR:</b>	19		

### Dimensions:

