



STL442

DIRECT / IN-DIRECT SUSPENDED LINEAR



The STL442 is a sophisticated ceiling-mounted LED luminaire that offers both direct and indirect light distribution. It features a robust anodized aluminium housing, available in sleek black or white satin finishes, complementing various interior styles. The UV-stabilized frosted diffuser ensures optimal light transmittance while reducing glare. Integrated within the housing is a DALI driver with an option of a 3-hour emergency pack for enhanced functionality. Available in two colour temperature options—3000K or 4000K—the LED PCB boards provide a CRI greater than 80, ensuring vibrant and accurate colour rendering for a range of environments.

Product Information

LENGTH OPTIONS:	POWER:	COLOUR TEMPERATURE:	OUTPUT:	EFFICIENCY:
600mm	14W / 8W	3000K	1345lm / 665lm	96lm/w
600mm	14W / 8W	4000K	1402lm / 721lm	100lm/w
900mm	21W / 14W	3000K	2040lm / 1345lm	97lm/w
900mm	21W / 14W	4000K	2111lm / 1402lm	100lm/w
1200mm	26W / 21W	3000K	2585lm / 2040lm	99lm/w
1200mm	26W / 21W	4000K	2648lm / 2111lm	101lm/w
1500mm	32W / 26W	3000K	3230lm / 2585lm	100lm/w
1500mm	32W / 26W	4000K	3318lm / 2648lm	103lm/w
BODY:	White ● Black		LIFETIME:	60,000hrs
COLOUR TEMPERATURE:	3000K ● 4000K		DIFFUSER:	UV Frosted
DIMMING:	Switched ● DALI		INPUT:	230-240V
CRI:	>80		MATERIAL:	Anodised Aluminium
IP RATING:	IP40			
EMERGENCY:	3hr Kit (Optional)			
BINNING SDCM:	3			
UGR:	19			



Dimensions:

